



Remix Dry Mortar Ltd, C5 Premier Business Centre, Newgate Lane, Fareham,
Hampshire, PO14 1TY
13

BS EN 998-1:2016

Prescribed factory made natural and/or coloured general purpose rendering/
plastering mortar for internal and external use.

Production Plant:	Avonmouth, Bristol	
Proportion of Constituents (C:L:S / C:S - By Volume)	1:1½:4-4½	1:1:5-6
Cement	15%	13%
Lime	3.0%	4%
Sand	82%	83%
Compressive Strength Category	CS IV	CS IV
Reaction to Fire:	Class A1	Class A1
Adhesion	0,20 N/mm ² – FP: A	0,10 N/mm ² – FP: A
Water Absorption	W1	W1
Thermal Conductivity $\lambda_{10, dry}$:	0,67 W/mK (tab. mean value; P = 50%)	0,47 W/mK (tab. mean value; P = 50%)
Water Vapour Permeability Coefficient μ :	15	15
Durability:	Suitable for use in Severe exposure conditions, dependent on good site practice and provisions detailed in BS EN 13914-1:2016	Suitable for use in Moderate exposure conditions, dependent on good site practice and provisions detailed in BS EN 13914-1:2016

Signed:

Rakesh Nar.....
Technical Manager
For and on behalf of
Remix Dry Mortar Ltd